



1562SC Series

Semi-Concealed Electromagnetic Shear Locks

SDC's HiShear® electromagnetic shear locks are designed, engineered and built in America for openings that require an architecturally superior appearance. Long recognized as a cut above alternatives on the market, SDC shear locks provide high security with a failsafe locking mechanism to meet a variety of door opening applications.

SDC's 1562SC series semi-concealed configuration incorporates the innovative HiShear® concealed electromagnetic lock with a surface mounted armature assembly. The semi-concealed design also provides the advantage of mounting the HiShear® on the secure side of the door opening, eliminating potential for tampering.

- Concealed mortise lock and surface mount armature design
- Floating armature assembly
- Special alloy steel shear tabs
- Auto-sensing dual voltage
- Door alignment relock sensor
- Adjustable lateral and vertical alignment
- Noise dampeners

ORDERING GUIDE

	FINISH	
	V	
	Y	
	C	
	X	
	Q	
	P	
1562SCHDB	V	D L
1562SC		D
1562SCHDB		L
1562SCHDB3/4		
MODEL		OPTIONS

NOT REQUIRED 

EXAMPLES

1562SCV	Semi-Concealed Shear, External Electronics, 2000lbs, 628	1,103.00
1562SCVD	Semi-Concealed Shear, External Electronics, 2000lbs, 628, DPS	1,167.00
1562SCVDL	Semi-Concealed Shear, External Electronics, 2000lbs, 628, DPS, LED	1,189.00
1562SCHDBV	Semi-Concealed 1/2" Glass Door Shear, External Electronics, 2000lbs, 628	1,366.00
1562SCHDB3/4V	Semi-Concealed 3/4" Glass Door Shear, External Electronics, 2000lbs, 628	1,366.00

COMPONENT CONSIDERATIONS

With a robust toolbox of over 35,000 SDC access & control components at your fingertips, you can add additional components to complement the products you're ordering and assemble a turnkey solution for almost any controlled door opening system imagined.



Keypads & Readers
Page 112-116



Egress Devices
Pages 129-133



Exit Switches & Sensors
Pages 134-145



Emergency Door Releases
Page 146



Power Controllers
Pages 153-164



Door Controllers
Page 165



Remote Control Consoles
Pages 166-167



Door Prop Alarms & Annunciators
Page 168-169

1562SC CONFIGURATION 1 of 1

MODEL		● ○ ○	LIST \$
1562SC	Semi-Concealed Shear Lock, External Electronics, 2000lbs		1,103.00
1562SCHDB	Semi-Concealed 1/2" Glass Door Shear Lock, External Electronics, 2000lbs		1,366.00
1562SCHDB3/4	Semi-Concealed 3/4" Glass Door Shear Lock, External Electronics, 2000lbs		1,366.00

FINISH		○ ● ○	ADD TO LIST
V	628 Dull Aluminum <small>Standard</small>		N/C
Y	335 Dull Black		102.00
C	605 Bright Brass		130.00
X	710 Dark Bronze		102.00
Q	626 Dull Chrome		242.00
P	625 Bright Chrome		242.00

OPTIONS		○ ○ ●	ADD TO LIST
D	Door Position Status (DPS)		64.00
L*	Visual Status Indicator (LED)		22.00

*Mounts separately through the frame and may be used to indicate lock is engaged or wired to monitoring contacts.